

## BZ-202 Wetting Dispersant

**composition:** High molecular block polymer

**Appearance:** Light yellow transparent liquid

**Active content:** 100%

**Application range:** : industrial coatings, wood coatings, anticorrosive coatings, coil coatings, ink and so on

**Recommended dosage:** inorganic pigment: 1.0-5.0%; organic pigment: 10-50%; total amount: 0.2-2.0%

**Usage:** In order to obtain full effect, please test the most appropriate amount before use and add it before grinding.

### Features and advantages:

1. It has a special wetting effect on bentonite precast slurry and can coordinate the activation of precast slurry with good fluidity.
2. It has a good dispersion and anti-settling effect on the filler, which can reduce the surface tension between pigment and base material, improve the wetting capacity of base material and pigment, strengthen the grinding effect and reduce the dispersion time.

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** : Carefully evaluate the relative amount of use before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.