

BZ-202F Dispersant

Composition: Inlaid modified polyether compound

Appearance: Colorless transparent liquid

Active ingredient: 50%

Application range: : industrial coatings, wood coatings, automotive coatings, anticorrosive coatings;

Recommended dosage: titanium dioxide: 1-3%; organic pigment: 3-10%; carbon black: 20-40%; total amount: 0.1-0.5%

Usage: In order to get the full effect, it is recommended to add it in two periods.

Features and advantages:

1. The titanium dioxide is well dispersed, especially in the alkyd resin, with good wetting and dispersion, excellent viscosity reduction, short dispersion time, no flocculation after uniform dispersion, and excellent whiteness of the dispersed titanium dioxide.
2. In the system with more pigments and fillers, the amount of pigments and fillers can be increased to maintain good viscosity. It has a good effect on the wetting dispersion and fluidity of various pigment colors (such as red, phthalocyanine blue, phthalocyanine green, etc.).
3. It also has good dispersion and surface tension reduction effect in industrial paint and wood paint.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: : Carefully evaluate the relative amount of use before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.