

BZ-2110A titanium dioxide dispersant

Composition: a polymer block copolymer containing a pigment group

Appearance: Pale yellow transparent liquid

Active: 50%

Application range: industrial coating, epoxy coating, wood coating, coil coating, automotive coating

Recommended dosage: full amount inorganic pigment, organic pigment, carbon black

0.3%-2%

1%-20%

20%-30%

30%-80%

Use :

In order to obtain full effect, the resin and solvent should be pre-mixed, then the additives should be added slowly under stirring until uniform dissolution, and the pigments should be added after the additives. Please test the appropriate amount before use.

Features and advantages:

1. Good dispersion of titanium dioxide, reduce the viscosity of titanium dioxide, good whiteness and very good coverage.
2. It has good wettability to pigment filler and can increase the anti-settling function of coating system.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: carefully evaluate the specific amount in the coating system before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.