

## BZ-2193 Wetting Dispersant

**Composition:** polyester modified special compound

**Appearance:** Light yellow transparent liquid

**Active portion:** 40%

**Application range :** industrial coatings, epoxy coatings, wood coatings, coil coatings, ink and so on

**Recommended dosage:** titanium dioxide, organic pigment, carbon black, full amount

5-6%	10-20%	30-50%	0.3-1.5%
------	--------	--------	----------

### Use :

In order to obtain full effect, the resin and solvent should be pre-mixed, then the additives are added slowly under stirring until they are dissolved evenly, and the pigments are added after the additives. Please test the appropriate amount before use.

### Features and advantages:

1. It has excellent wetting and viscosity reduction effect, and has a good dispersion effect on titanium dioxide, red, blue, green and carbon black, which reduces the grinding time of pigment and is not easy to return to roughness.
2. It is stable for all kinds of pigments and suitable for preparing pigment concentrated paste. It has good resin solubility, can reduce viscosity and provide flow, especially suitable for epoxy system.

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** The color of this product may be darkened during long-term storage, which is normal and will not affect the performance.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.