

BZ-4010 Wetting Dispersant

Composition: a polymer block with a pigment group

Appearance: colorless to yellowish transparent liquid

Active portion: 50%

Application range : industrial coating, wood coating, automotive coating, anticorrosive coating, coil coating

Recommended dosage: inorganic pigment: 1.0-5.0%; organic pigment: 10-50%; total amount: 0.1-0.5%

Usage: In order to obtain full effect, please test the appropriate amount before use and add it before grinding.

Features and advantages:

1. General strength, good solubility with various resins, dispersion ability outstanding;
2. Good wetting, reduce grinding time; prevent floating color and blooming, improve the coloring power of pigment;
3. The powder dispersion, anti-settling and arrangement are excellent, which increases the coverage of titanium dioxide and increases the whiteness,
Improve the gloss of the coating system;

Package: 25KG non-recyclable blue barrel.

The product is not completely used. The lid must be tightly closed after use.

Storage: keep away from heat source, light source and avoid light.

Precautions: carefully evaluate the specific amount in the coating system before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.