

BZ-263A, General Color Paste Dispersant

Composition: a polymer block copolymer containing a pigment group

Appearance: Pale yellow transparent liquid

Active portion: 50%

Application range: PU coating NC coating, industrial coating, automotive coating

Recommended dosage: full amount inorganic pigment, organic pigment, carbon black

| | | | |
|----------|-------|--------|--------|
| 0.1–0.5% | 1–20% | 20–30% | 30–80% |
|----------|-------|--------|--------|

Usage: The resin and solvent should be pre-mixed, then the additives are added slowly under stirring until they are dissolved evenly.

The pigment is added after the additive is added.

Features and advantages:

1. It has a good dispersion and anti-flocculation effect on pigment, increases the gloss of coating, reduces viscosity and reduces grinding time;
2. Enhance the transparency of transparent pigments and the covering power of solid color pigments;
3. Can reduce the tension between pigment or filler and resin, prevent floating color and blooming.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: The color of this product may be darkened during long-term storage, which is normal and will not affect the performance.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.