

BZ-268 Wetting Dispersant

Composition: a polymer block copolymer containing a pigment group

Appearance: Light yellow transparent liquid

Active portion: 50%

Application range: PU coating, NC coating, UN coating, epoxy coating, industrial coating, ink, etc

Recommended dosage:

Inorganic pigment:1-20%

Organic pigment:20-50%

Carbon black:20-100%

Full amount:0.1-1.0%

Usage:

The resin and dispersant should be pre-mixed, then the solvent should be added slowly under stirring until it is dissolved evenly. The pigment should be added after the additive is added. Please test the appropriate amount before use.

Features and advantages:

1. It is especially suitable for the dispersion of high pigment and medium pigment carbon black, with excellent viscosity reduction and very good color development. The ground carbon black paste is darker and brighter than other dispersants, and the color is more vivid.
2. It also has excellent dispersion performance for titanium dioxide, which can effectively reduce the viscosity of the system and improve the whiteness of titanium dioxide.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: carefully evaluate the specific amount in the coating system before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.