

## BZ-2335 Wetting Dispersant

**Composition:** polyurethane polymer compound

**Appearance:** Yellow transparent liquid

**Active portion:** 50%

**Application range :** industrial coating, wood coating, automotive coating, anticorrosive coating ink

**Recommended dosage:** full amount inorganic pigment, organic pigment, carbon black

0.1–0.5%

1–20%

20–30%

50–200%

**Usage:** The resin and dispersant should be pre-mixed, then the solvent should be added slowly under stirring until it is dissolved evenly. The pigment should be added after the additive is added. Please test the appropriate amount before use.

### Features and advantages:

- 1、 Suitable for solvent-based industrial coatings and automotive coatings polymer dispersants.
- 2、 The pigment and carbon black are dispersed well, and the viscosity of the polished color paste is stable, which is not easy to return to coarseness and flocculation.
- 3、 Suitable for resin free color paste, improve the color development of organic pigments, and effectively reduce the viscosity of high concentration color paste in grinding.

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** Keep away from heat source, fire source and light.

**Precautions:** The color of this product may be darkened during long-term storage, which is normal and will not affect the performance.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.