

BZ-2609 A Slurry Dispersant

Composition: Modified polyurethane polymer

Appearance: Yellow to dark yellow transparent liquid

Active portion: 50%

Application range: UV system, Alkyd system polyurethane system, Acrylic system polyester system, Chlorinated acetic acid system

Recommended dosage: All inorganic pigments, organic pigments, carbon black

0.1–1%	1–10%	10–50%	10–100%
--------	-------	--------	---------

Usage: The resin and dispersant should be pre-mixed, then the solvent should be added slowly under stirring until it is dissolved evenly. The pigment should be added after the additive is added. Please test the appropriate amount before use.

Features and advantages:

- 1、 It has a good dispersion effect on industrial paint with high filler content, and is especially suitable for the wetting and dispersion of dull powder in the system with high dull powder content. It can reduce the viscosity of dull coating with high dull powder content, improve the efficiency of matting, and make the matting agent well oriented.
- 2、 It has excellent anti-sinking effect, improves the storage stability of coating, and stabilizes the pigment in light curing printing ink. It is also suitable for preparing pigment concentrated paste.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: carefully evaluate the specific amount in the coating system before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.