

BZ-2431A Wetting Dispersant

Composition: Acrylic block copolymer

Appearance: Pale yellow transparent liquid

Active portion: 100%

Application range: industrial coatings, wood coatings, automotive coatings, ink, water-based industrial coatings.

Recommended dosage: All inorganic pigments, organic pigments, carbon black

0.1–0.5%

1–20%

20–30%

30–80%

Usage: The resin and dispersant should be pre-mixed, then the solvent should be added slowly under stirring until it is dissolved evenly.

The pigment should be added after the additive is added. Please test the appropriate amount before use.

Features and advantages:

1. It has a wide range of compatibility with various resin systems and is suitable for the dispersion of carbon black and pigment in industrial paint, automotive paint and ink system.
2. It is especially suitable for acrylic system color paste grinding, and the blackness and gloss of the carbon black paste are particularly excellent after grinding.
3. The dispersed color paste has good fluidity and excellent color development, and will not return to coarse or false thick.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, fire source and light.

Precautions: The color of this product may be darkened during long-term storage, which is normal and will not affect the performance.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.