

BZ-2062 titanium dioxide dispersant

Composition: polymer

Appearance: colorless to yellowish transparent liquid

Active portion: 65±2%

Application range: polyurethane system, acrylic system, epoxy system, alkyl acid system, low polarity system, UV system

Recommended dosage: All titanium dioxide organic pigment

0.1–1.0% 1–3% 3–10%

Usage: The resin and dispersant should be pre-mixed, then the additive is added slowly under stirring until it is dissolved evenly. The pigment is added after the additive is added. Please test the appropriate amount before use.

Features and advantages:

1. The titanium dioxide dispersion has excellent whiteness, good covering power, no flocculation after uniform dispersion, and excellent storage stability.
2. It has a good effect on the wetting and dispersion of various color paste pigments (such as red, phthalocyanine blue, phthalocyanine green, etc.) and fluidity.
3. Good control effect of floating color to prevent floating color from blooming.

Package: 25KG non-recyclable barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: Carefully evaluate the specific amount in the system before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.