

## BZ-4141 Benzene-Free Defoamer

**Composition:** Balloon polymer and modified polysiloxane solution

**Appearance:** colorless transparent liquid

**Active portion:** 20%

**Application range:** solvent based coating, light curing coating, solvent free coating.

**Recommended dosage:** Total formula 0.1-1.0% (test the most appropriate dosage before use)

**Usage:** To achieve sufficient defoaming effect, it is recommended to add before grinding.

If added later, mix under sufficiently high shear force.

To ensure the good distribution of defoamer.

### Features and advantages:

- 1、 With excellent defoaming and foam suppression effect, it can suppress and eliminate the bubbles produced in the process of production, canning and construction of coatings, Prevents the formation of pinholes, etc., and is effective for spraying, brushing and roller coating.
- 2、 In a variety of base material systems, it has good transparency, and can maintain strong defoaming effect without affecting the transparency of clear varnish

Suitable for high, clear and transparent coating system.

**Package:** 25KG/180KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Carefully evaluate the effects on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.