

## BZ-404D High Solid Acrylic Defoamer

**Composition:** Pure propylene ester polymer

**Appearance:** Colorless to light yellow transparent liquid

**Active portion:**  $\geq 75\%$

**Application range:** solvent coating; light curing coating, solvent-free coating.

**Recommended dosage:** Total formula 0.1-0.5% (test the most appropriate dosage before use)

**Usage:** In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, mix under a sufficiently high shear force to ensure the defoaming effect.

### Features and advantages:

1、 With excellent defoaming and foam suppression effect, it can suppress and eliminate the bubbles produced in the process of production, canning and construction of coatings,

It is especially effective in eliminating bubbles generated by the reaction of two-component coatings and in eliminating foaming in high zinc stearate formulations.

2. It is used for matte surface and primer to eliminate foam, which does not affect the heavy coating and adhesion, and will not produce shrinkage holes.

**Package:** 25KG/180kg non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.