

BZ-505D High Solid Acrylic Defoamer

Composition: pure acrylic polymer (high molecular weight)

Appearance: colorless to light yellow transparent liquid

Activity score: 85%±2

Application range : solvent-based coating; light curing coating, solvent-free coating.

Recommended dosage: Total formula 0.1-0.5% (test the most appropriate dosage before use)

Usage: In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, it should be mixed under a sufficiently high shear force to ensure the defoaming effect.

Features and advantages:

1. Excellent defoaming and foam suppression effect, can inhibit and eliminate the bubbles produced in the process of production, canning and construction of coatings;

It is especially effective in eliminating bubbles generated by the reaction of two-component coatings and in eliminating foaming in high zinc stearate formulations.

2. It has long-term stability and can maintain defoaming performance for a long time without affecting the recoating and adhesion, and will not produce shrinkage holes.

Package: 25KG/180kg non-recyclable blue barrel.

The product is not completely used. The lid must be closed tightly after use.

Storage: keep away from heat source, light source, and avoid light storage.

Precautions: Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.