

# BZ-066N Special Organic Silicon Defoamer

**Composition:** Fluorinated modified siloxane

**Appearance:** colorless to yellowish transparent liquid

**Non-volatile matter:** 2.0%

**Application range:** solvent coating, light curing coating, solvent-free coating;

**Recommended dosage:** Total formula 0.05-0.5% (test the most appropriate dosage before use)

**Usage:** To achieve sufficient defoaming effect, it is recommended to add before grinding. If added later, mix under sufficiently high shear force to ensure the good distribution of defoamer.

## Features and advantages:

1. It has the performance of eliminating and suppressing foam efficiently, and has a very high effect on eliminating micro bubbles in coating products.
2. It is especially suitable for white paint and color paint to eliminate foam effect, and has a good effect on the elimination of UV roller coating machine foam.

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Carefully evaluate the effects on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.