

# BZ-410 Strong Fluorine-Containing Defoamer

**Composition:** Fluorinated modified siloxane

**Appearance:** colorless or yellowish liquid

**Active ingredients:** 2%

**Application range:** Suitable for: solvent-based coatings; Recommended for: light curing coatings, solvent-free coatings;

**Recommended dosage:** 0.1-0.8% of the total formula

**Usage:** Can be added at any time.

## Features and characteristics:

- 1、 It has good solubility with various resin systems and excellent defoaming and foaming breaking effect. It has a very high defoaming effect on both micro bubbles and large bubbles in coating products.
- 2、 Strong fluorine-containing defoamer has a wide range of general use, can be applied to a variety of common coating systems, and has good solubility in different application systems. It is suitable for polyester, short oil alcohol acid, chlorinated rubber, polyurethane, epoxy, acrylic, nitrocellulose, acid curing coatings.

**Package:** 25KG non-recyclable blue barrel.

The product has not been used completely. After use, the inner and outer covers must be tightly closed.

**Storage:** keep away from heat source, fire source and light.

**Precautions:** Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.