

## BZ-411B Defoamer

**Composition:** Modified silicone compound

**Appearance:** colorless to yellowish transparent liquid

**Non-volatile matter:** 2.0%

**Application range :** solvent based coating, light curing coating, solvent free coating.

**Recommended dosage:** Total formula 0.1-1.0% (test the most appropriate dosage before use)

**Usage:** In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, mix under a sufficiently high shear force to ensure good distribution of the defoamer.

### Features and advantages:

- 1、The solubility of BZ411B in various resin systems is better than that of BZ410, and it has excellent defoaming and foaming inhibiting effects. It has a very high defoaming effect on the microbubbles in coating products.
- 2、It has the solubility that other types of defoamers can not compare, and is especially suitable for medium and high polarity clear paint, matte paint, white paint, PE series.

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.