

BZ-4920 Defoamer

Composition: does not contain silicone organic polymer

Appearance: Yellow transparent liquid

Active portion: 100%

Application range: solvent coating, light curing coating, solvent-free coating, printing ink, etc.

Recommended dosage: Total formula 0.3-1.0% (test the most appropriate dosage before use)

Usage: Pre-dilute with the recommended reagent for easy addition and mixing. It can be added during grinding or paint mixing. Stir before use. It can be added to the clear coat formula.

Features and advantages:

1. Good solubility, suitable for high viscosity and high solid content coatings, light curing coating defoaming agent.
2. Can inhibit the production of microbubbles in the coating, eliminate the bubbles produced during the manufacturing and stirring of the coating.
3. Suitable for dip coating, roller coating and spraying, high degassing efficiency, high solubility, suitable for clear paint and color paint, good recoating, no silicone.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.