

BZ-4194 Polyester Defoamer

Composition: polyester defoaming polymer (non-silicon)

Appearance: colorless transparent liquid

Active portion: 100%

Application range: solvent-based coatings, light curing coatings, solvent-free coatings, printing inks, adhesives, etc.;

Recommended dosage: Total formula 0.1-0.8% (test the most appropriate dosage before use)

Usage: In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, mix under a sufficiently high shear force to ensure good distribution of the defoamer.

Features and advantages:

1. It has excellent defoaming and foaming inhibiting effect, which can suppress and eliminate the bubbles produced in the process of production, canning and construction of coatings, and prevent the occurrence of pinholes.
2. It belongs to non-silicon type defoamer, and has the incomparable solubility of other types of defoamer. It has good compatibility with various resin systems, and does not affect the re-coating, especially suitable for medium and high polarity clear varnish system, and will not be cloudy.

Package: 25KG non-recyclable blue barrel.

The product is not completely used. The lid must be closed tightly after use.

Storage: keep away from heat source, light source, and avoid light storage.

Precaution: Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.