

## BZ-6889 Silicone Defoamer

**Composition:** silicone defoaming polymer

**Appearance:** milky white liquid

**Active portion:** 100%

**Application range:** solvent based coating; light curing coating, solvent free coating.

**Recommended dosage:** Total formula 0.1-1.0% (test the most appropriate dosage before use)

**Usage:** In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, mix under a sufficiently high shear force to ensure the defoaming effect.

**Features and advantages:**

1. It has a good inhibiting and defoaming effect on the bubbles generated during the manufacturing and construction of high solid content and solvent-free epoxy coatings or screen printing inks.
2. It has a very high defoaming efficiency, which can show excellent defoaming effect with very little addition, and at the same time, it can still keep the dyne value of the paint film at a high level even when excessive addition is added, so as to minimize the impact of subsequent recoating.
3. It has a wide range of applications, such as epoxy potting compound, two-component epoxy system, light curing ink, floor paint, etc.

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.