

BZ-6801 Silicone Defoamer

Composition: Deflated polysiloxane solution

Appearance: Colorless to yellowish transparent liquid

Active portion: 15%

Application range : solvent based coating, light curing coating, solvent free coating.

Recommended dosage: Total formula 0.05-0.5% (test the most appropriate dosage before use)

Usage:

In order to achieve full defoaming effect, it is recommended to add before grinding. If added later, mix under a sufficiently high shear force to ensure good distribution of the defoamer.

Features and advantages:

- 1、 With efficient defoaming and foam suppression performance, it can reduce the foam produced in the production and processing of epoxy resin and polyurethane system, so as to obtain a bubble-free surface.
- 2、 It has a very high defoaming effect on the micro bubbles in the paint products, and is especially suitable for white paint and color paint.
- 3、 It has a good effect on eliminating the spray and roller coating machine bubble.

Package:

The 25KG blue bucket is not recycled.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: Carefully evaluate the effects on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.