

## BZ-603-1 Acrylate leveling agent

**Composition:** Polypropylene acid solution

**Appearance:** Colorless to yellowish transparent liquid

**Active ingredients:** 70%

**Application range:** Furniture paint, Coil coating, Can coating, Industrial baking paint, Ink and so on

**Recommended dosage:** 0.1-0.5% of the total formula (test the most appropriate dosage before use)

**Usage:** can be added at any time in the production process, please test before use.

**Features and advantages:**

1. It has the properties of defoaming and leveling, improves the leveling and gloss, does not affect the re-coatability or interlayer adhesion, can reduce the surface tension between the coating substrate, and solve the pinhole and orange peel phenomenon caused by the increase of coating viscosity.
2. It can also improve the wetting and anti-foaming effect on the substrate for high temperature paint.

**Package:** 25KG non-recyclable blue barrel.

The product is not completely used. The lid must be tightly closed after use.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Please carefully evaluate before use, and the requirements must be tested to determine.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.