

BZ-603B Is an Acrylic leveling agent with defoaming properties

Composition: Polyacrylate solution

Appearance: Colorless to yellowish transparent liquid

Active content: 50%

Application range: PE furniture paint, Coil coating, Can coating, Industrial baking paint

Recommended dosage: 0.1-0.5% of the total formula

Usage: can be added at any time in the production process, please test before use.

Features and advantages:

1. Due to its non-polar structure, it has both leveling and defoaming properties. It is especially designed for the significant reduction of reaction bubbles in PE paint after adding white water, so the defoamer can be added less in the formula system.
2. Improve leveling and gloss, without affecting the re-coatability or interlayer adhesion, can reduce the surface tension between the coating substrate, solve the pinhole and orange peel phenomenon caused by the increase of coating viscosity.
3. It has super wetting properties and can also prevent the coating from blooming.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: Please carefully evaluate before use, and the requirements must be tested to determine.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.