

BZ-608 Anti-Cratering Leveling Agent

Composition: Modified silicone

Appearance: Colorless to yellowish viscous liquid

Active portion: 100%

Application range: Solvent based coating, Light curing coating, Water based coating

Recommended dosage: Total formula 0.1-0.5% (test the most appropriate dosage before use)

Usage: can be added at any time in the production process, please stir evenly, please test before use.

Features and advantages:

- 1、 It has high surface activity and good wettability to the substrate, which can eliminate the phenomena of shrinkage hole, crater, pinhole and sandblasting trace on the underlying layer, so that the coating film can be leveled.
- 2、 It has good stability and strong anti-puncture ability in all coating systems.
- 3、 In the water system, improve the leveling, recoating, anti-evaporation, anti-adhesion, adhesion and coating fog resistance.

Package: 25KG non-recyclable blue barrel.

The product is not completely used. The lid must be tightly closed after use.

Storage: keep away from heat source, light source and avoid light.

Precautions: Please carefully evaluate before use, and the requirements must be tested to determine.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.