

## BZ-6310 Polyester Leveling Agent

**Composition:** polyester compound

**Appearance:** colorless transparent liquid

**Active portion:** 45±2%

**Application range:** solvent coating, wood coating, light curing coating, car paint, industrial baking paint.

**Recommended dosage:** Total formula 0.1-1.0% (test the most appropriate dosage before use)

**Usage:** It can be added at any time during the production process, including after addition. Please stir evenly and test before use.

### Features and advantages:

1. Excellent solubility with most systems, good recoatability, and no effect on interlayer adhesion;
2. Good substrate wettability, effectively reduce surface tension, and do not stabilize bubbles;
3. The leveling type is between short wave leveling and long wave leveling. While the leveling speed is fast, it can improve the fullness of the paint film;
4. Good temperature resistance, no surface defects of paint film due to degradation under high temperature conditions;

**Package:** 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Please carefully evaluate before use. It is suitable for matte, primer and bright light.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.