

BZ-6190 Polyester Leveling Agent

Composition: Polyester compound

Appearance: Colorless transparent liquid

Active portion: 92%±1%

Application range: Solvent based coating, Wood coating, Light curing coating, Car paint, Industrial baking paint

Recommended dosage: 0.1-1.0% of the total formula (test the most appropriate dosage before use)

Usage : can be added at any time in the production process, including after addition, please stir evenly, please test before use.

Features and advantages:

1. Excellent solubility with most systems, good recoatability, and no effect on interlayer adhesion;
2. Good substrate wettability, effectively reduce surface tension, and do not stabilize bubbles;
3. The leveling type is between short wave leveling and long wave leveling. While the leveling speed is fast, the fullness of the paint film can be improved;
4. Good temperature resistance, no surface defects of paint film due to degradation under high temperature conditions;

Package: 25KG non-recyclable blue barrel.

The product is not completely used before use. The lid must be tightly closed after use.

Storage: keep away from heat source, fire source and light.

Precautions: Please carefully evaluate before use. It is suitable for matte, primer and bright light.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.