

# BZ-610 Organosilicon general leveling agent

**Composition:** Fluorinated modified silicone

**Appearance:** Colorless to yellowish transparent liquid

**Active portion:** 15%

**Application range:** Solvent coating, Wood coating, Light curing coating

**Recommended dosage:** Total formula 0.1-1.0% (test the most appropriate dosage before use)

**Usage:** can be added at any time in the production process, please test before use.

## Features and advantages:

1. Suitable for PU glossy and matte, with good solubility, which can reduce surface tension.
2. The molecular positioning of the base silicone is neat, and it can be leveled quickly, so that the smoothness of the coating surface is greatly improved and the gloss is improved.
3. It has good compatibility with most resins, high interfacial activity, and good wettability to the substrate, which can eliminate the phenomenon of frame.

**Package:** 25KG non-recyclable blue barrel.

The product is not completely used before use, and the lid must be tightly closed after use.

**Storage:** keep away from heat source, light source and avoid light.

**Precautions:** Please carefully evaluate before use. It is suitable for matte, primer and bright light.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.