

BZ-8377 Fluorinated Modified Acrylic Leveling Agent

Composition: Fluorinated modified acrylic polymer

Appearance: Colorless transparent liquid

Active portion: 70%

Application range: Wood coatings, High temperature baking paint, Coil coating, light curing coating, Epoxy coating

Recommended dosage: Total formula 0.1-0.6% (test the most appropriate dosage before use)

Usage: can be added at any time in the production process, please test before use.

Features and advantages:

1. It is a fluorine modified polymer leveling agent with excellent leveling and recoating properties.
2. It can prevent the formation of shrinkage and fish eye, and obtain the best flow and flatness.
3. It can enhance the wetting effect on the substrate, have a plasticizing effect and prevent the generation of bubbles.
4. On rainy days, PE paint has the effect of leveling and anti-fog.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: Keep away from heat source, fire source and light.

Precautions: Please carefully evaluate before use, and the requirements must be tested to determine.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.