

BZ-6378 Fluorinated Modified Acrylate Leveling Agent

Composition: Fluorinated modified acrylic ester

Appearance: Colorless to yellowish transparent liquid

Active portion: 70%

Application range: Solvent based coating, Wood coating, Light curing coating, Industrial baking paint

Recommended dosage: Total formula 0.1-1.0% (test the most appropriate dosage before use)

Usage: can be added at any time in the production process, including after addition, please stir evenly, please test before use.

Features and advantages:

- 1、 It is suitable for various solvent-based coatings to prevent shrinkage and leveling additives, increase gloss and make the coating produce long wave leveling effect, reduce surface tension, and do not affect the heavy coating and interlayer adhesion.
- 2、 It has high compatibility and high permeability, which will not cause turbidity in clear paint and haze in colored paint.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, fire source and light.

Precautions: Please carefully evaluate before use. It is suitable for matte, primer and bright light.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.