

BZ-661 Polyacrylate leveling agent

Composition: polyacrylate solution

Appearance: colorless transparent liquid

Active portion: 100%

Application range: solvent coating, wood coating, light curing coating, car paint, industrial baking paint

Recommended dosage: Total formula amount 0.1-1.0% (the most appropriate amount should be tested before use)

Usage: It can be added at any time during the production process, including after addition. Please stir evenly and test before use.

Features and advantages:

1. Suitable for all kinds of solvent-based coatings shrinkage and leveling additives, can improve the flow and leveling, eliminate the defects of shrinkage, pinholes, fish eyes and other defects in the coating film;
2. It has defoaming performance and good thermal stability, which makes the coating produce long-wave leveling effect, reduce surface tension, increase gloss, and does not affect the heavy coating and interlayer adhesion.

Package: 25KG non-recyclable blue bucket.

The product is not completely used. The lid must be closed tightly after use.

Storage: keep away from heat source, fire source, and avoid light storage.

Precautions: Please carefully evaluate before use. It is suitable for matte, primer and bright light.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.