

BZ-6600 High-fluorine leveling agent

Composition: Fluorocarbon polymer compound

Appearance: Colorless transparent liquid

Active portion: 70%

Application range: Furniture paint, car paint, Baked enamel paint, Printing iron coating, Two-component epoxy system.

Recommended dosage: Total formula amount 0.1-0.5% (test the most appropriate dosage before use)

Usage: can be added in the early or late stage of production, please stir evenly, please test before use.

Features and advantages:

1. Fluorocarbon modified leveling agent can greatly improve the content of fluorocarbon, and more effectively reduce the surface tension of various organic coating systems, rapid substrate wetting speed, more efficient and lower consumption.
2. Eliminate surface defects, have no adverse effect on the overall performance of the paint film, and have good solubility, outstanding anti-puncture effect, and very good flow effect.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: Keep away from heat source, fire source and light.

Precautions: Please carefully evaluate before use. It is suitable for matte, primer and bright light.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.