

BZ323-5 Contains Defoaming Leveling Agent

Composition: Aryl modified polymethyldialkylsiloxane

Appearance: Colorless transparent liquid

Active portion: 100%

Application range: solvent-based coating, light curing coating, polyurethane coating, nitrocellulose coating

Recommended dosage: Total formula 0.1-0.5% (test the most appropriate dosage before use)

Usage: It can be added at any time in the production process, please test before use.

Features and advantages:

- 1、The defoaming or foam suppression effect of the silicone leveling agent with defoaming function depends on the polarity of the coating system.
- 2、Fast leveling effect, reduce surface tension and smoothness, does not affect the heavy coating.
- 3、The thermal stability is excellent, and the interlayer adhesion of the coating is not affected even at 280°C.
- 4、In matte coatings and metal coatings, the orientation of the matting powder and aluminum powder is improved to improve the arrangement of the matting powder and aluminum powder,
And it will not cause gloss increase.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, fire source and light.

Precautions: Please carefully evaluate before use, and the best requirements must be determined after testing.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.