

BZ-333 Polyether Modified Leveling Agent

Composition: polyether modified silicone polymer

Appearance: colorless to yellowish transparent liquid

Active portion: $\geq 98\%$

Application range: solvent coating, industrial coating, wood coating, automotive coating, ink

Recommended dosage: Total formula 0.05-0.8% (test the most appropriate dosage before use)

Usage: can be added at any time in the production process, please test before use.

Features and advantages:

- 1、Excellent solubility, water and oil universal, fast leveling, can strongly reduce the surface tension of paint and printing ink, improve the wetting effect of substrate.
- 2、It has a good ability to prevent shrinkage, pinholes, bubbles and orange peel and other surface defects.
- 3、It can improve the lubricity of the substrate, smoothness of the surface, and gloss of the coating. In the aqueous system, it can also improve the anti-adhesion.

Package: 25KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: Please carefully evaluate before use, and the best requirements must be determined after testing.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.