

BZ-6356 Leveling Agent

Composition: Silicone modified acrylic ester solution

Appearance: Colorless to yellowish transparent liquid

Active content: 100%

Application range: Solvent based coating, Light curing coating, Solvent free coating.

Recommended dosage: Total formula 0.05-0.5% (test the most appropriate dosage before use)

Usage: It can be added at any time during the production process, including after addition. Please stir evenly and test before use.

Features and advantages:

- 1、 Combined with the characteristics of silicone leveling agent and acrylic leveling agent, that is, short wave and long wave leveling, it has the effect of rapid leveling and improving the flatness of paint film, and reduces the occurrence of surface defects such as orange peel and shrinkage.
- 2、 It has good compatibility with various resins, can improve the wetting and adhesion of the substrate, and has good recoatability, low stability and good feel.
- 3、 The leveling agent contains hydroxyl functional groups, which can react with crosslinking agents to obtain lasting feel, especially suitable for UV curing system, wood coatings and automotive coatings;

Package :

The 25KG blue bucket is not recycled.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, light source and avoid light.

Precautions: Carefully evaluate the effects on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.