

RS-270 Wetting Agent

Composition: polyether modified polysiloxane

Appearance: Pale yellow transparent liquid

Active portion: 100%

Application range: Automotive paint, Industrial coating, Architectural coating, Wood coating, Printing ink and varnish, Inkjet ink;

Recommended dosage: Total formula 0.1-1.0% (test the most appropriate dosage before use)

Usage: It can be added directly to the system or diluted before use.

Features and advantages:

1. Excellent leveling, wetting and spreading ability and permeability, effectively reduce the surface tension of the coating, so that the coating can better wet various substrates, such as plastic, metal, glass, wood, etc., to ensure the uniform spreading of the coating on the substrate surface.
2. The shrinkage hole effect is good, which can prevent the defects such as shrinkage hole and pinhole caused by uneven surface tension during the drying process of the coating, so that the coating surface is more smooth and flat.
3. Improve the flow and leveling of the coating, reduce orange peel, brush marks and other leveling problems, and improve the gloss and beauty of the coating.

Package: 25KG/200kg non-recyclable blue barrel.

The product is not completely used. The lid must be closed tightly after use.

Storage: keep away from heat source, light source, and avoid light storage.

Precautions: Carefully evaluate the effect on solubility and crater before use.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.