

201P-1 Polyethylene Wax Anti-Suspension

Composition: Polyethylene wax

External Appearance: white paste

Active content: 10%

Application range: Industrial coating, Wood coating, Automotive coating

Recommended dosage : Total formula amount 0.5-2.0% (test the most appropriate dosage before use)

Usage : can be added at any stage of the production process, no grinding is required, but must be dispersed under high speed stirring.

Features and advantages:

- 1、The high molecular weight wax anti-settling agent can be directly dispersed into the system to provide excellent anti-settling effect without affecting the viscosity of the system.
- 2、It has no obvious effect on the gloss, yellowing resistance and drying speed of the film, and can improve the touch of the coating film.
- 3、It can be used as a post-additive without grinding, especially suitable for pigments and color pastes that cannot be ground.
- 4、At the same time, it can help the direction arrangement of matte powder and aluminum silver powder in the paint film, especially suitable for matte paint, pearlescent paint, aluminum powder paint and other industrial coatings, wood coatings and automobile coatings.

Package: 50KG non-recyclable blue barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: Keep away from heat source, fire source and light.

Precautions: 201P-1 is used for aluminum powder paint, it should be dispersed in resin first, and then add aluminum paste.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.