

690 Polyamide Wax Anti-Sediment

Composition: Polyamide wax

Appearance: Pale yellow paste

Active content: 20%

Solvents: Xylene, ethanol

Application range: Polyurethane coating, Light curing coating, Coil coating, Epoxy paint

Recommended dosage: Total formula amount 0.5-2.0% (test the most appropriate dosage before use)

usage method :

1. It is recommended to use the pre-gel method to pre-mix the wax slurry and solvent to make a pre-gel.
2. The pre-dispersing equipment should use a high speed disperser, do not use sand mill and other high shear equipment.
3. The pre-dispersion temperature is generally suitable for 20°C-40°C, and the time is 30-40 minutes.

Features and advantages:

Polyamide wax anti-settling is added to coatings, inks and adhesives to form a strong network structure, with excellent thixotropic properties and good dispersion, anti-sagging, anti-settling and thickening effects. It is suitable for furniture paint, automotive paint, high solid, thick coating paint effective.

Package: 16KG non-recyclable barrel.

The lid must be tightly closed after use if the product is not completely used.

Storage: keep away from heat source, fire source and light.

Precautions: Please carefully evaluate before use, and the requirements must be tested to determine.

The above information is based on the product situation. Due to different producer formula, production process and construction conditions, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company reserves the right to improve its products and any changes in specifications will not be notified in advance.